



GREASE & SPOT REMOVER

DESCRIPTION:

A natural product, which is completely biodegradable. It is a citrus solvent degreaser, which can be used in many industrial cleaning applications. It is non-corrosive and contains no harmful chlorinated solvents, petroleum distillates, acids or alkali. It will remove oil, grease and tar from most surfaces and will leave a fresh citrus scent.

USE:

Grease & Spot Remover can be used to remove deposits of grease, oil, and other fluid spills from concrete surfaces. It dissolves most resins, adhesives, rubber tire marks, and a variety of other tough compounds on floors and industrial equipment. Grease & Spot Remover is packaged ready to use, with no mixing or adding required. This product is considered a non-polluting, biodegradable degreaser; it emits a mild citrus odour while it degreases and cleans.

LIMITATIONS:

May be harmful to some plastics and painted surfaces. Test surface in a inconspicuous area before using. Should not be used on conductive floors.

TECHNICAL DATA:**Typical Properties**

Colour	Lt. Orange
Odour	Light citrus
Specific Gravity	0.88
Flash point	50°C (PMCC)
Freezing Point	-40°C
Boiling Point	165°C

SURFACE PREPARATION:

Sweep floor with a stiff bristled broom to remove surface dirt and other loosely adhering solid contaminants.

DIRECTIONS:

Wear protective gloves. For most applications such as degreasing equipment, oil spill cleanup, removal of tar and asphalt, Grease & Spot is to be used at full strength. For light degreasing the product may be diluted with water, but will reduce the effectiveness.

Oil, Rubber tire marks, Asphalt, Tar, and Mastic:

Apply at full strength. Allow 15 to 20 minutes for penetration and heavy cleaning. **Do not allow material to dry on surface.** Scrub with a stiff bristled brush. Thoroughly rinse with high pressure, clean potable water. The higher the water pressure the deeper the cleaning action. All traces of grease and oil should be removed. For unusually deep seated grease and oil stains, a second application may be necessary and allow to remain on surface for 20 to 30 minutes. Again do not allow to dry.

General-purpose cleaning:

Grease & Spot Remover may be diluted with up to 2 parts water, depending on severity of the cleaning job. Brush or apply with a trigger sprayer for use on printers ink, resins, chewing gum and adhesives.

CLEAN UP:

Clean tools with water.

PACKAGING:

1 Litre Containers
4 Litre Containers
20 Litre Containers
205 Litre Containers

REV. 11/24/08