



## **RAPID REPAIR PRIMER**

### **DESCRIPTION:**

Rapid Repair Primer is a non-reemulsifiable liquid bonding primer for use in cement based overlay materials. Rapid Repair Primer is used to improve the bond of cement based overlay materials on a properly prepared concrete surface. It also seals porous concrete surfaces preventing pinholes and out gassing bubbles from forming in the finished surface.

### **SURFACE PREPARATION:**

Concrete or other surfaces to be overlaid must be clean and structurally sound. New concrete and masonry surfaces must be cured a minimum of 7 days. Remove all laitance and weak, loose or faulty concrete. Remove all oil, grease, asphalt or other foreign matter.

### **MIXING AND APPLICATION:**

Shake or mix well to ensure that there is no settlement. Apply primer at 200 square feet per gallon to the surface and work into the concrete surface with a stiff-bristle push broom. Spread evenly to thoroughly coat the surface taking care to avoid any puddling.

Wood or excessively porous or absorbent surfaces should be double primed. Allow primer to dry between coats.

Allow primer to dry clear before application of the overlay material. Lower temperatures or a high humidity environment will require a longer dry time. Apply overlay material within 4 hours of the primer application.

### **CLEAN UP:**

Clean tools and equipment with detergent and water immediately following use. Clean drips, spills, and smears while primer is still wet.

### **STORAGE AND HANDLING:**

**Keep from freezing.** Do not apply in temperatures below 10°C (50°F). Clean tools soon after use with water. If swallowed, rinse mouth thoroughly. Drink plenty of water, and consult a doctor immediately. If splashed in eyes or on skin flush thoroughly with water. Keep out of reach of children.

### **WARRANTY:**

Seller warrants that the product described on the face hereof has been manufactured of selected raw materials by skilled technicians. Neither seller nor manufacturer shall be responsible for any claims resulting from the failure to utilize the product in the manner in which it was intended and in accordance with instructions provided for use of product. The only obligation of either the seller or manufacturer shall be to replace any quantity of this product which proved to be defective. Neither seller nor manufacturer assumes any liability, loss, or damage resulting from use of this product.

REV 5/02/18

**Notice to User** - Con-Spec Industries Ltd. warrants that the product described on the face hereof has been manufactured of selected raw materials by skilled technicians. Con-Spec Industries Ltd. shall not be responsible for any claims resulting from the failure to utilize the product in the manner in which it was intended and in accordance with instructions provided for use of product. The only obligation of Con-Spec Industries Ltd. shall be to replace any quantity of this product which proved to be defective. Con-Spec Industries Ltd. assumes no liability, loss, or damage resulting from use of this product. **Your use of this product constitutes your acknowledgment and acceptance of these terms and limitations.**