

SAFETY DATA SHEET

SECTION 1: IDENTIFICATION

PRODUCT NAME: CIPADECK[®] CURE & SEAL (LS)

MANUFACTURER/SUPPLIER: CPD Construction Products
219 Connie Crescent, Unit #13
Concord, Ontario Canada L4K 1L4

24 HOUR EMERGENCY NUMBER: CANUTEC: (613) 996-6666

APPLICATION AND USE: Low solids concrete curing and sealing compound formulated to meet OTC –
V.O.C. requirements.

PRODUCT DESCRIPTION: Single component penetrating sealer.

SECTION 2: HAZARDS IDENTIFICATION

GHS CLASSIFICATION Flammable liquid- 2 ; Skin irritation- 2 ; Eye irritation -2 ; Aspiration hazard- 1 ;
Specific target organ toxicity (single exposure)- 3 -central nervous system;
Specific target organ toxicity (repeated exposure)- 2 - kidney, liver, spleen, blood



SIGNAL WORD **DANGER**

HAZARD STATEMENTS H226 Flammable liquid and vapour.
H315 Causes skin irritation.
H320 Causes eye irritation.
H336 May cause drowsiness or dizziness.
H373 May cause damage to organs through prolonged or repeated exposure.

PRECAUTIONARY STATEMENTS

PREVENTION P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.
P261 Avoid breathing fumes/gas/mist/vapours/spray.
P273 Avoid release to the environment.
P280 Wear protective gloves/clothing/eye protection.

RESPONSE P302+P362+P352 IF ON SKIN: Take off contaminated clothing. Wash with
plenty of water.
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes.
Remove contact lenses, if present and easy to do. Continue rinsing.
P304+P340 IF INHALED: Remove person to fresh air and keep comfortable
for breathing.
P301+P310+P331 IF SWALLOWED: Immediately call a POISON CENTER/
doctor. Do NOT induce vomiting.

OTHER HAZARDS Flammable vapours may spread long distances/ may ignite explosively. Use
spark-proof tools and conductive shoes to avoid sparking hazards.

SECTION 3 : COMPOSITION/INFORMATION ON INGREDIENTS

| Hazardous Ingredients | % | C.A.S. # | LD/50, Route, Species | LC/50, Route, Species |
|--------------------------------------|-------|------------|--|---|
| Acetone | 30-60 | 67-64-1 | >5,800 mg/ Kg (Oral-Rat) | Not Available |
| Tertiary Butyl Acetate | 5-10 | 540-88-5 | 2,733 mg/ Kg (Oral-Rat) >2,000 mg/ Kg (Dermal-Rabbit) | >14,100 ppm (4hrs.) (Inhalation-Rat) |
| Petroleum Naphtha, Light Aromatic | 10-30 | 64742-95-6 | 5,000-8,400 mg/ Kg (Oral-Rat) 14,000 mg/ Kg (Dermal-Rabbit) | 3,670 ppm (4hrs.) (Inhalation-Rat) |

SDS-395
Revised October 8th, 2017

SAFETY DATA SHEET

Page 2

SECTION 4 : FIRST-AID MEASURES

FIRST-AID MEASURES

| | |
|--|--|
| EYE CONTACT | Flush eyes with lukewarm water for at least 15 minutes. Get immediate medical attention thereafter. |
| SKIN CONTACT..... | Wash with soap and water and remove contaminated clothing. Wash clothing separately prior to reuse. If irritation persists, get medical attention. |
| INHALATION | Remove victim to fresh air. If not breathing, give artificial respiration. If breathing is difficult give oxygen and continue to monitor. Get immediate medical attention. |
| INGESTION | If swallowed, DO NOT induce vomiting. Rinse mouth and call a physician or poison control centre immediately. Never give anything by mouth to an unconscious person. Stomach contents should be evacuated quickly in a manner which avoids aspiration. |
| SYMPTOMS AND EFFECTS, ACUTE OR DELAYED | |
| EYE CONTACT | Mild irritation and discomfort, may cause conjunctivitis and corneal damage when absorbed into the eye tissue. |
| SKIN CONTACT..... | Irritation may occur. Prolonged or repeated contact may result in skin sensitization and dermatitis due to the fatting. |
| INHALATION | Prolonged inhalation may result in respiratory irritation, dizziness, nausea and loss of consciousness. Get immediate medical attention. |
| INGESTION | Ingestion may cause severe gastrointestinal irritation, headache, nausea, vomiting |
| CHRONIC | Repeated and/or prolonged exposures may result in: adverse skin effects (de fatting, rash or allergic reaction/sensitization), adverse eye effects (conjunctivitis) and temporary liver and kidney damage. |
| IMMEDIATE MEDICAL ATTENTION AND SPECIAL TREATMENT NEEDED | Get medical attention if symptoms occur. |

SECTION 5: FIRE-FIGHTING MEASURES

| | |
|--|--|
| GENERAL FIRE HAZARDS | This product is classified as flammable category 3 (NFPA). Vapours may travel to source of ignition and flash back. Vapours may settle in low or confined spaces. May produce a floating fire hazard. Static ignition hazard can result from handling and use. |
| SUITABLE EXTINGUISHING MEDIA | Use carbon dioxide or dry chemical media for small fires. Use alcohol-type or all-purpose foam for large fires. Use water spray to cool fire exposed containers. Re-ignition is possible. Use water spray to disperse the vapours. |
| UNSUITABLE EXTINGUISHING MEDIA | No data available. |
| SPECIAL PROTECTION EQUIPMENT FOR FIRE FIGHTERS | Use self-contained breathing apparatus and protective clothing for large fires. |
| HAZARDOUS COMBUSTION PRODUCTS | Toxic gases may be formed during fire, smoke, carbon oxides, aldehydes. |

SECTION 6: ACCIDENTAL RELEASE MEASURES

| | |
|---|--|
| PERSONAL PRECAUTIONS, PROTECTIVE EQUIPMENT AND EMERGENCY PROCEDURES | Stop leak and isolate spill from all ignition sources. Avoid all contact with eyes, skin or clothing. Do not breath in vapours or fumes. Use appropriate personal protection equipment (PPE). |
| ENVIRONMENTAL PRECAUTIONS | Prevent entry to drains, sewers and public waters. |
| CONTAINMENT AND CLEAN UP | Contain/absorb spilled product with dry sand or earth. Do not use combustible materials such as sawdust. Dispose of clean up materials as hazardous waste in accordance with all provincial, state and federal laws. |

SECTION 7: HANDLING AND STORAGE

| | |
|-------------------------------------|--|
| PRECAUTIONS FOR SAFE HANDLING | Ground containers when transferring to sprayers. Keep containers closed when not in use. Keep containers out of direct sunlight. Once product is used, leave container lids off to allow all solvent to evaporate. |
|-------------------------------------|--|

SAFETY DATA SHEET

CONDITIONS FOR SAFE STORAGE Store in a cool dry area out of direct sunlight and away from all sources of ignition. Open pails containing product must be sealed prior to storing. Do not store full or part pails in direct sunlight.

SECTION 8: EXPOSURE CONTROLS / PERSONAL PROTECTION

| OCCUPATIONAL EXPOSURE LIMITS: | <u>ACGIH TLV</u> | <u>OSHA PEL</u> | <u>NIOSH IDLH</u> |
|---------------------------------------|---|---|---|
| ACETONE | TWA-250 ppm STEL-500 ppm | TWA-1800 mg/m ³ STEL-2400 mg/m ³ | IDLH-2500 ppm TWA-250 ppm TWA-590 mg/m ³ |
| TERTIARY BUTYL ACETATE | TWA-200 ppm | TWA-200 ppm TWA-950 mg/m ³ | TWA-200 ppm TWA-950 mg/m ³ |
| APPROPRIATE ENGINEERING CONTROL | Good ventilation should be assured to maintain vapours concentration below exposure limits. A portable eye wash station is recommended at the job site. | | |
| PERSONAL PROTECTIVE EQUIPMENT: | | | |
| EYE / TYPE | Splash proof chemical goggles are recommended. | | |
| RESPIRATORY PROTECTION | Concentrations in air determine the level of respirator protection needed. Use only NIOSH certified equipment. A half mask air purifying respirator with organic vapour cartridge is recommended. | | |
| GLOVES/TYPE | Neoprene or natural rubber gloves are required for protection of hands. | | |
| CLOTHING/TYPE | Standard coveralls. Always remove any contaminated clothing and wash before reuse. | | |
| FOOTWEAR/TYPE | Solvent resistant safety shoes/boots. | | |
| OTHER INFORMATION | Do not eat, drink or smoke when handling this material. | | |

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

| | |
|--|-----------------------------------|
| PHYSICAL STATE | Liquid |
| APPEARANCE | Clear or slight yellow |
| ODOUR | Camphor like odour |
| ODOUR THRESHOLD | 71 ppb |
| pH LEVEL | Not applicable |
| EVAPORATION RATE | 6.3 (Butyl Acetate =1) |
| BOILING POINT | 56°C (133°F) Acetone |
| FREEZING/MELTING POINT | Not Available |
| FLASH POINT (deg C), METHOD..... | -20°C (-4°F) Tag Closed Cup (TCC) |
| FLAMMABLE LIMITS IN AIR | 2.5-13.0% (by volume) |
| AUTO IGNITION TEMPERATURE (deg C) | 465°C (869°F) |
| VAPOUR PRESSURE (mmHg)..... | 180 @ 20°C (68°F) |
| VAPOUR DENSITY | 2.0 (air=1.0) |
| SOLUBILITY IN WATER | Insoluble |
| SPECIFIC GRAVITY @20°C (68°F)..... | 0.840 |
| V.O.C. Content | < 350 grams/L |
| PERCENT SOLIDS | 16 -19% |

SECTION 10: STABILITY AND REACTIVITY

| | |
|-------------------------------------|--|
| REACTIVITY | Stable under normal use conditions. |
| CHEMICAL STABILITY | Material is stable under normal use conditions. |
| POSSIBILITY OF HAZARDOUS REACTIONS: | Hazardous polymerization will not occur under normal conditions. |
| CONDITIONS TO AVOID | Avoid direct sunlight, heat, sparks, open flame or other ignition sources. |
| INCOMPATIBLE MATERIALS | Avoid contact with strong acids and strong oxidizing compounds. |
| HAZARDOUS DECOMPOSITION PRODUCTS: | Carbon oxides (CO, CO ₂), smoke, aldehydes. |

SAFETY DATA SHEET

SECTION 11: TOXICOLOGICAL INFORMATION

EXPOSURE ROUTES/ SYMPTOMS AND EFFECTS

| | |
|-----------------------------------|---|
| INGESTION | Product may be harmful or fatal if swallowed. Ingestion may cause central nervous system effects including dizziness, unconsciousness, coma or death. |
| INHALLATION | High concentrations may lead to central nervous system effects (drowsiness, dizziness, nausea, headaches, paralysis and loss of consciousness and even death). High vapour concentrations are irritating for eyes, nose, throat, lungs. |
| EYE CONTACT | Contact with the eye may cause moderate to severe irritation. |
| SKIN CONTACT | Moderately irritating to the skin. Prolonged or repeated contact can result in defatting and drying of the skin which may result in skin irritation and dermatitis. |
| PRE-EXISTING CONDITIONS | The following diseases or disorders may be aggravated by exposure to this product: skin, eye, lung (asthma-like conditions). |
| CARCINOGENICITY OF MATERIAL | Not applicable |
| REPRODUCTIVE EFFECTS | TOXIC. |

SECTION 12: ECOLOGICAL INFORMATION

| | |
|-------------------------------------|---|
| ECOTOXICITY | No data available. |
| PERSISTENCE AND DEGRADABILITY | This product is not expected to persist in the environment. |
| BIOACCUMULATIVE POTENTIAL | No data available. |
| MOBILITY IN THE SOIL | No data available. |

SECTION 13: DISPOSAL CONSIDERATIONS

| | |
|------------------------|--|
| PRODUCT DISPOSAL | Recover and recycle if possible. Otherwise: incineration in a permitted facility. Product in the liquid state is hazardous material and must be disposed of in accordance with all Provincial, State and Federal laws. Do not allow product to enter sewers, streams or lakes. |
| WASTE DISPOSAL | Empty containers of this product that are dry (no solvent) can be disposed of as normal garbage. |

SECTION 14: TRANSPORTATION INFORMATION

| | |
|--------------------------|--|
| TDG CLASSIFICATION | Paint Related Material, UN1263, Class 3, PG II |
|--------------------------|--|

SECTION 15: REGULATORY INFORMATION

| | |
|-------------------------------|-------------------------|
| WHMIS CLASSIFICATION | B2, D2A, D2B |
| CPR (CANADA) COMPLIANCE | Meets all requirements. |

SECTION 16: OTHER INFORMATION

| | |
|-------------------------|--|
| ACGIH | American Confederation of Governmental Industrial Hygienists |
| IARC..... | International Agency for Research on Cancer |
| NTP..... | National Toxicology Program |
| STEL | Short Term Exposure Limit |
| PEL | Permissible Exposure Limit |
| TLV-TWA | Threshold Limit Value - Time-Weighted Average |
| OSHA | Occupational Safety and Health Administration |
| NIOSH | National Institute for Occupational Safety and Health |
| CPR | Controlled Products Regulations |
| CAS | Chemical Abstracts Service |
| PREPARED BY: | Camelia Gardo |
| TELEPHONE NUMBER: | (905) 669-5013 |
| PREPARATION DATE: | October 8 th , 2017 |

The above information pertains to this product as currently formulated, and is based on the information available at this time. Addition of reducers or other additives to this product may substantially alter the composition and hazards of the product. Since conditions of use are outside our control, we make no warranties, express or implied, and assume no liability in connection with any use of this information.