

RAPID REPAIR MIXING LIQUID

DESCRIPTION:

Rapid Repair Mixing Liquid is a ready to use nonreemulsifiable liquid bonding admixture for use with cement based materials. Rapid Repair Mixing Liquid is used to improve the flexural, adhesion, durability, freeze/thaw resistance, and salt scaling of cement based materials. It can be used in cement based coatings, toppings, patches, levelling compounds, stucco, terrazzo, and mortar mixes.

SURFACE PREPARATION:

Concrete or other surfaces to be topped or parged must be clean and structurally sound. New concrete and masonry surfaces must be cured 7 days. Remove all weak, loose or faulty concrete. Remove all oil, grease, asphalt or other foreign matter. Wet down substrate concrete prior to application of topping but leave no standing water.

USE:

Use full strength as the mixing liquid for the patching or overlay material. Shake or mix well to ensure that there is no settlement. See mixing instructions of the patching material for amount of liquid needed. Place the patching or mortar quickly and trowel to the desired thickness. Avoid overworking the final finish.

CLEAN UP:

Clean tools and equipment with detergent and water immediately following use. Clean drips, spills, and smears while mix is still wet. Mixes containing Rapid Repair Mixing Liquid are extremely difficult to remove if allowed to dry before cleaning.

STORAGE AND HANDLING:

Keep from freezing. Do not apply in temperatures below $5^{\circ}C(40^{\circ}F)$. Clean tools soon after use with water.

SAFETY PRECAUTIONS:

Skin sensitizer. Avoid splashing into eyes or contact with skin. In case of eye contact, flood eyes repeatedly with water and call a physician immediately. DO NOT RUB EYES! Wash hands thoroughly with soap and clean water after handling. If swallowed rinse mouth and drink plenty of water, see doctor immediately. If splashed in eyes or on skin flush thoroughly with water. Keep out of reach of children. Consult Safety Data Sheet for further information.

REV 9/12/19

Notice to User - Con-Spec Industries Ltd. warrants that the product described on the face hereof has been manufactured of selected raw materials by skilled technicians. Con-Spec Industries Ltd. shall not be responsible for any claims resulting from the failure to utilize the product in the manner in which it was intended and in accordance with instructions provided for use of product. The only obligation of Con-Spec Industries Ltd. shall be to replace any quantity of this product which proved to be defective. Con-Spec Industries Ltd. assumes no liability, loss, or damage resulting from use of this product. Your use of this product constitutes your acknowledgment and acceptance of these terms and limitations.