Con-Spec Industries Ltd.

# SAFETY DATA SHEET

## **SECTION 1. IDENTIFICATION**

Product Name: So Other Means of Identification: Si

Sure Step SIL SS-1

Recommended Product Use: Restrictions on Use:

**Classification:** 

Slip resistant additive None known

#### Manufacturer/Importer/Supplier/Distributor Information:

Company:	Con-Spec Industries Ltd.	
Address:	9525 - 63 Avenue NW	
	Edmonton, Alberta T6E 0G2	
Contact:	Robert Lummerding	
Telephone:	1 (780) 437-6136	
Fax:	1 (780) 437-5242	
E-Mail:	conspec@shaw.ca	

Emergency Telephone: CANUTEC (613) 996-6666

## **SECTION 2. HAZARD(S) IDENTIFICATION**

Not a Hazardous Product Regulation (EC) No 1272/2008

Combustible dust

Label Elements: Signal Word: Hazard Statement:	None None		
Hazards Not Otherwise Class may ignite flammable atmospheres. H (See Dust Hazard Reference in Section	ligh levels of product dust in the atmosphere may present a dust explosion hazard.		
Labelling of special preparations (GHS): EYE CONTACT HEALTH RISKS AND SYMPTOMS OF EXPOSURE: Particulates may cause mechanical eye			
irritation. Flush eyes with copious amounts of water for at least 15 minutes. <b>SKIN CONTACT HEALTH RISKS AND SYMPTOMS OF EXPOSURE:</b> Negligible dermal irritant. Exposure may lead to itching, scaling, drying and irritation of skin.			
INGESTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE: Generally non toxic unless large quantities are ingested.			
HEALTH HAZARDS (ACUTE & CHRONIC):			
	ligh concentrations of polymer fumes may cause eye, nose and respiratory irritation, lizziness or unconsciousness.		
CHRONIC EFFECTS:	Repeated skin contact can lead to drying, defatting, itching, stinging and irritation.		
MEDICAL CONDITIONS GENERALLY AGGREVATED BY EXPOSURE: May irritate people with skin problems, asthma and lung diseases. Susceptible individuals may have an allergic reaction.			



### Page 2 / 6

## SAFETY DATA SHEET SURE STEP

## **SECTION 3. COMPOSITION / INFORMATION ON INGREDIENTS**

Mixtures:

Chemical Identity	CAS Number	Content in Percent (%)*
Polypropylene homopolymer	9003-07-0	100

**Composition comments:** \*All concentrations are percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

## **SECTION 4. FIRST-AID MEASURES**

#### **Inhalation:** Treat as a nuisance dust. Remove victim to fresh air and provide oxygen if breathing is difficult. Immediate medical attention not normally required. No delayed effects expected.

#### **Skin Contact:** For skin irritation, wash skin with soap and water and use emollient skin cream.

- **Eye Contact:** Flush with copious amounts of water for at least 15 minutes. IMMEDIATE MEDICAL ATTENTION IS NECESSARY.
- **Ingestion:** Not a normal or expected route of introduction. If large quantities are ingested IMMEDIATE MEDICAL ATTENTION IS NECESSARY. Do not give anything to an unconscious person.

Instruction for Physicians: No specific advice. Treat according to symptoms present.

## **SECTION 5. FIRE-FIGHTING MEASURES**

General Fire Hazards: Combustible solid (OSHA Flammability Class)

**Suitable Extinguishing Media:** Carbon Dioxide, dry chemical or fine water spray. Avoid water stream on molten burning material as it may scatter and spread the fire.

Specific Hazards Arising from the Chemical:	Flash point >530 F 277 C. Melts in proximity to fires, causing slippery floors and stairs. When powder is suspended in air, these products could be FLAMMABLE/EXPLOSIVE. In these circumstances, keep away from heat, sparks and open flames. Static charges on powders or powders in liquids may ignite flammable atmospheres. See Section 7 "HANDLING AND STORAGE" for suggestions on how to use these products under such conditions. Also refer to NFPA Bulletin 654, "Prevention of Fire and Dust Explosions in the Chemical, Dye, Pharmaceutical, and Plastics Industries", for safe handling procedures.
Special Fire Fighting	Wear add contained brothing apparetus and protective elething approved by

Special Fire FightingWear self-contained breathing apparatus and protective clothing approved byProcedures:NIOSH. Watch footing on floors and stairs because of possible melting and<br/>spreading of material. Use spray to keep containers cool.

**Con-Spec** Industries Ltd.

# SAFETY DATA SHEET SURE STEP

Page 3 / 6

## SECTION 6. ACCIDENTAL RELEASE MEASURES

#### STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:

Wear recommended personal protective equipment. Remove ignition sources. Sweep up with a minimum of dusting. Keep away from heat or flame. Collect in containers (e.g. fiberboard drums or cartons). If hot liquid, attempt to confine spill and let the polymer solidify. Once solid, it may be recovered as the powder. Report major leaks and spills to the appropriate local, state and federal government agencies.

#### HAZARD WARNING

These products are micronized powders. Static charges on the powders may ignite flammable atmospheres. High levels of product dust in the atmosphere may present a dust explosion hazard. (See Dust Hazard Reference in Section 16. Read Section 7.) See the Regulatory Information (Section 15) regarding reporting requirements.

## **SECTION 7. HANDLING AND STORAGE**

**Precautions for Safe Handling:** (Always wear recommended personal protective equipment.) Avoid spillage which can cause very slippery conditions on floors. Use good personal hygiene and housekeeping.

**Conditions for Safe Storage,** Avoid excessive heat. Do not store near strong oxidizing agents and amines. **Including any Incompatibilities:** 

#### STATIC ELECTRICITY AND FINE PARTICLE SIZE WAXES

Electrostatic charges of non-conductive materials is a natural phenomenon ranging from harmless to a nuisance to a hazard, depending on the degree of charging and the environment where the discharge takes place. In the case of micronized polymers and waxes, very high levels of static electricity develop in their manufacture, transportation and handling. These products, being poor conductors of electricity, can and will hold a static charge for long periods of time. With this in mind, a great deal of care should be exercised when handling this type of product in or around flammable liquids, particularly if the liquid is at or near its flashpoint. The generation of static electricity cannot be prevented because its intrinsic origins are present at every particle interface. Some common sense approaches to the hazards involved with static electricity are as follows:

- Use only conductive equipment and keep all components grounded and bonded to the same vessel in order to equalize any potential charge.

- Avoid projections and probes that could lead to discharge between the charged polymer and probe.

- Avoid a flammable condition by the use of inert gases in the container or by providing sufficient exhaust so as to prevent a buildup of flammable solvent vapors.

- Never pour micronized polymers or waxes from a drum or large container directly into hot flammable solvents.

- Add micronized polymers or waxes slowly and in small quantities to hot flammable solvents.

- Do not permit the product to free fall directly into the solvent. Use a pipe or chute that leads down to the level of the solvent. Make sure the pipe or chute is grounded and bonded.

- If mechanical equipment must be used, a slow-turning screw feeder that is grounded and is preferred.

- Good housekeeping is of prime importance. The building and equipment should be designed to eliminate shelves and ledges and similar places where materials can accumulate.

The above are only suggestions and should not be taken as recommended practices in your establishment and in no way should be considered as comprehensive engineering controls. A more detailed discussion and recommended practices can be found in NFPA 77 issued by the National Fire Protection Association Inc. in 1988.

# SAFETY DATA SHEET SURE STEP

Page 4 / 6

## SECTION 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

#### **Control Parameters Occupational Exposure Limits**

Chemical Name	Туре	Exposure Limit Values	Source
Polypropylene homopolymer	TLV / TWA	10 mg/m3	ACGIH
Polypropylene homopolymer	PEL	5 mg/m3 (Respirable Fraction)	OSHA

Consult local authorities for provincial or state exposure limits.

ACGIH® = American Conference of Governmental Industrial Hygienists. TLV® = Threshold Limit Value. TWA = Time-Weighted Average. STEL = Short-term Exposure Limit. A4 = Not classifiable as a human carcinogen. OSHA = US Occupational Safety and Health Administration. PEL = Permissible Exposure Limits. OEL = Occupational Exposure Limits. REL: Recommended Exposure Limit

#### Appropriate Engineering Controls:

Use adequate ventilation during heating processes or if dusty conditions Prevail when handling powdered materials. For storage and ordinary handling, general ventilation is adequate.

**Eye Protection:** Safety glasses with side-shields.

Skin Protection: Protective gloves,

**Respiratory:** Use a NIOSH approved dust respirator with product.

#### Individual Protection Measures, such as Personal Protective Equipment General Information:

Wash skin thoroughly with soap and warm water after handling and before smoking, eating or applying makeup. If clothes become contaminated, change to clean clothing. Do not wear contaminated clothing until properly laundered. Further information relating to the safe handling and use of fluorocarbon polymers may be found in DWE (NIOSH), Publication No. 77-193.

## **SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

Appearance		
Physical State:	Powder	
Form:	Solid	
Color:	White	
Odour:	Not Applicable	
Odour Threshold:	Not Applicable	
PH:	Not Applicable	
Melting Point/Freezing Point:	166°C (330°F)	
Initial Boiling Point and Boiling Range:	Not Applicable	
Flash Point:	>277°C (450°F) COC	
Evaporation Rate:	Not Applicable	
Flammability (solid, gas):	Combustible Solid	
<b>Upper/Lower Limit on Flammability or Explosive Limits</b> 450°F TOC		

Con-Spec Industries Ltd.

Page 5 / 6

# SAFETY DATA SHEET SURE STEP

Vapor Pressure:	1
Vapor Density:	ł
Relative Density:	(
Solubility(ies)	
Solubility in Water:	1
Solubility (other):	1
Partition Coefficient (n-octanol/water):	ι
Auto-ignition Temperature:	ι
Decomposition Temperature:	ι
Volatiles (%):	(

NIL Heavier than air. 0.90 g/cc

NIL NIL Unknown Unknown Unknown 0

## **SECTION 10. STABILITY AND REACTIVITY**

Reactivity:	Stable at normal conditions.
Chemical Stability: Possibility of Hazardous Reactions:	Hazardous polyermization should not occur.
Conditions to Avoid:	Extreme heat, sparks and open flame.
Incompatible Materials:	Strong oxidizing agents and amines.
Hazardous Decomposition Products:	These products may emit oxides of carbon and nitrogen.

## **SECTION 11. TOXICOLOGICAL INFORMATION**

Acute Toxicity / Effects: Acute toxicity	No data developed	
Oral:	No data developed. Aspiration is possible.	
Inhalation:	No data developed. None expected. Treat as nuisance dust.	
Dermal:	No data developed. None expected. Treat as nuisance dust.	
Eye:	No data developed. Treat as nuisance dust.	
Chronic Toxicity/Effects Repeated dose toxicity:	STOST-single exposure : No data developed. Treat as nuisance dust. STOST-repeated exposure : No data developed. Treat as nuisance dust.	
Genetic toxicity: Mutagenicity:	No data developed No Data Developed	
Carcinogenicity:	No	
Reproductive toxicity:	No	

**Medical Conditions Generally Aggrevated by Exposure:** May irritate people with skin problems, asthma and lung diseases. Susceptible individuals may have an allergic reaction.



Page 6 / 6

# SAFETY DATA SHEET SURE STEP

## SECTION 12. ECOLOGICAL INFORMATION

**Ecological Profile:** No data have been developed on this subject. These polymeric products are not soluble in water. They are not considered biodegradable. Potential environmental impact in case of spill or release is considered to be minimal to NIL.

## **SECTION 13. DISPOSAL CONSIDERATIONS**

**WASTE DISPOSAL METHOD:** Assume conformity with applicable disposal regulations. Preferred method of disposal is in closed containers of sufficient strength to eliminate leakage at approved incineration or chemical landfill waste disposal site in accordance with local regulations. Sewage disposal is discouraged.

The information offered here is for the product as shipped.

## **SECTION 14. TRANSPORT INFORMATION**

#### TDG:

UN Shipping Name:	Not Regulated
Classification:	N/A
UN:	N/A
Packing Group:	N/A

## **SECTION 15. REGULATORY INFORMATION**

WHMIS Classification:

Not subject to WHMIS regulations

## **SECTION 16. OTHER INFORMATION**

Other useful guides to handling organic powders include: NFPA 77 Recommended Practice on Static Electricity NFPA 654 Standard for the Prevention of Fire and Dust Explosions from the Manufacturing, Processing, and Handling of Combustible Particulate Solids NFPA 499 Recommended Practice for the Classification of Combustible Dusts and of Hazardous (Classified) Locations for Electrical Installations in Chemical Process Areas OSHA 3371-08 Hazard Communication Guidance for Combustible Dusts DUST HAZARD - Notification given pursuant to Table 1.5.2 of the 3rd Revision of GHS (2009).

Revision Date:	February 15, 2022
Version #:	1.1

#### Notice To Reader:

For Industrial Use Only. Keep out of Reach of Children. The information contained and opinions expressed herein are based on the available information to us and is believed to be correct at the date of this Safety Data Sheet. Con-Spec Industries Ltd., is not liable for any consequential, incidental, or special damages arising directly or indirectly from the use of this information. The use of this information and these opinions, and the conditions of the use of the product are not within the control of Con-Spec Industries Ltd., it is the user's obligation to determine the conditions for safe use of this product. We assume no responsibility for injury from the use of the product described herein.