



# GREASE & SPOT REMOVER

## DESCRIPTION:

Grease & Spot Remover is a ultra concentrated natural citrus degreaser which can be used in many industrial cleaning applications. It is a natural product which is completely biodegradable. It is non-corrosive and contains no harmful chlorinated solvents, petroleum distillates, acids or alkalis. Grease & Spot Remover will remove oil, grease, tar even tire marks from most surfaces, while leaving behind a fresh, citrus scent.

## USE:

Grease & Spot Remover can be used to remove deposits of grease, oil, and other fluid spills from concrete surfaces. It dissolves most resins, adhesives, rubber tire marks, and a variety of other tough compounds on floors and industrial equipment.

## LIMITATIONS:

May be harmful to some plastics and painted surfaces. Do not use on floor finishes, as it may remove the finish. Always pre-test surface in a inconspicuous area before using. Should not be used on conductive floors. If allowed to dry on a concrete surface a white stain will result that can only be removed by mechanical means.

## TECHNICAL DATA:

### Typical Properties

Colour	Clear Light Rust
Odour	Mild citrus
Specific Gravity	0.85
Flash point	52°C (TCC)
Freezing Point	-7°C
Boiling Point	161°C

## SURFACE PREPARATION:

Sweep floor with a stiff bristled broom to remove surface dirt and other loosely adhering solid contaminants.

## DIRECTIONS:

Wear protective gloves. For most applications such as degreasing equipment, oil spill cleanup, removal of tar and asphalt, Grease & Spot is to be used at full strength. For light degreasing the product may be diluted with water.

### Oil, Rubber tire marks, Asphalt, Tar, and Mastic:

Apply at full strength. Allow 5 minutes contact time for penetration and heavy cleaning. **Do not allow material to dry on surface.** Scrub with a stiff bristled brush. Thoroughly rinse with high pressure, clean potable water. The higher the water pressure the deeper the cleaning action. Use of high pressure hot water will clean more deeply. All traces of grease and oil should be removed. For unusually deep seated grease and oil stains, a second application may be necessary. Again do not allow to dry. Flush until water becomes clear (not white).

### General-purpose cleaning:

Grease & Spot Remover use diluted with up to 4-6 oz per gallon of warm water. Apply solution to surface, allow 3 to 5 minutes contact time. Rinse thoroughly with water.

## CLEAN UP:

Clean tools with water.

## PACKAGING:

1 Litre Containers  
1 US Gallon Containers  
5 US Gallon Containers

REV 09/29/23

**Notice to User** - Con-Spec Industries Ltd. warrants that the product described on the face hereof has been manufactured of selected raw materials by skilled technicians. Con-Spec Industries Ltd. shall not be responsible for any claims resulting from the failure to utilize the product in the manner in which it was intended and in accordance with instructions provided for use of product. The only obligation of Con-Spec Industries Ltd. shall be to replace any quantity of this product which proved to be defective. Con-Spec Industries Ltd. assumes no liability, loss, or damage resulting from use of this product. **Your use of this product constitutes your acknowledgment and acceptance of these terms and limitations.**